






# Toroidal transformer type 58017



serial operation to double the secondary voltage



parallel operation to double the secondary current



Power rating 160VA  
 Primary voltage 230VAC - 50/60Hz  
 Secondary voltages 2x 30V - 2.67A  
 Regulation 7%

Diameter 110mm  
 Height 43mm  
 Weight 1.9kg

Height and weight are measured without mounting materials  
 All leads are solid and approx 200mm long

Supplied mounting materials:  
 1 metal washer Ø90mm  
 2 neoprene washers Ø90mm  
 1 bolt M5x50mm with nut

With KEMA KEUR, ENEC, CE and UL/CSA approvals  
 KEMA certificate 96 2307, UL filenumber E320377.

Time lag fuses to be used.  
 Primary: 0.8A, 5x20mm, IEC127, high I<sup>2</sup>t value  
 Secondary: none



Industrieweg 14  
 NL-7161BX NEEDE  
 The Netherlands

P O - B o x 2 7  
 NL-7160AA NEEDE  
 The Netherlands  
 Tel.+31 (0)545 28 3456  
 Fax+31 (0)545 28 3457

info@amplimo.nl  
<http://www.amplimo.nl>

HB

Oct 2010

**58017**

**toroidal transformer  
 160VA**

© Copyright Amplimo BV